

258 EIGHT CHANNEL POWER AMPLIFIER



OVERVIEW

The Meridian 258 is our dedicated rack-mount Eight Channel Power Amplifier. This powerful, high performance, cool-running Class D amplifier is suitable for a wide range of applications and delivers >100W per channel into 4 ohms or >70W per channel into 8 ohms*.

At only 1U high, the compact 258 is a category changing amplifier; bringing Meridian high resolution sound quality to every zone it powers.

PRODUCT HIGHLIGHTS

- Featuring a highly efficient, cool and fanless construction, the Meridian 258 provides a truly 'fit and forget' solution when driving multiple zones. Its compact chassis also takes up minimal space in-rack, measuring just 1U high.
- An audiophile approach has been taken to the 258's component selection, resulting in a level of performance typically associated with power amplifiers offered at a significantly higher price.
- The adoption of an advanced linear power supply provides excellent isolation from the AC supply for excellent sound quality.
- The Meridian 258's short signal path delivers signal purity, while multilayer circuit boards provide the best electromagnetic performance.
- A ground plane design has also been chosen for optimal signal handling.



REAR PANEL LAYOUT

CONSTRUCTION

The featured high efficiency (>95%) Class D amplifiers produce very little heat. In conjunction with the aluminum construction, the 258 is easily cooled without the need for vents.

A new linear power supply has also been selected to provide isolation from the AC supply and offer both sound quality and intrinsic durability.

- **Separate reservoir capacitors** – offers the advantages of a multiple-mono construction in a compact package. This keeps signal paths very short and improves isolation between channels.
- **High performance components** – multilayer circuit boards with ground planes combined with audiophile-grade components deliver a category-leading quality of sound.

SPECIFICATION

AUDIO OUTPUTS	<ul style="list-style-type: none"> • 70W into 8 Ohms per channel at 10% THD • 100W into 4 Ohms per channel at 10% THD • Phoenix Connectors supplied for ease of installation 24-12 AWG cable
AUDIO INPUTS	<ul style="list-style-type: none"> • Eight RCA inputs
CONTROL	<ul style="list-style-type: none"> • REAR PANEL: Trigger input [3.5mm 5-30 VDC] • FRONT PANEL: On/Off Switch
DISPLAY	<ul style="list-style-type: none"> • LEDs to indicate 'Standby' [Blue], 'On' [White], 'Overload' [Red]
POWER	<ul style="list-style-type: none"> • Advanced linear power supply: 100V ac 50/60 Hz 110-120V ac 50/60Hz 220-240V ac 50/60Hz
DIMENSIONS	<ul style="list-style-type: none"> • HEIGHT: 44mm [1.73in] • WIDTH: 480mm [18.9in] • DEPTH: 360mm [14.17in] • WEIGHT: 5.5Kg [12.13lbs]
CONSTRUCTION	<ul style="list-style-type: none"> • All aluminium construction • Optional standalone feet pads supplied

*One channel driven at 10% THD